

8 7 6 5 4 3 2 1

- NOTES:**
1. ROHS COMPLIANT
  2. MATERIALS:  
 FIBER OPTIC:  $\varnothing$ 1.5MM OPTICAL CORE,  $\varnothing$ 2.2MM POLYETHYLENE CABLE JACKET  
 LENS MOUNT: OPTICAL GRADE ACRYLIC  
 LED MOUNTS: FOR SMD 22 & THR 22 - NYLON 66, UL RATING 94-V2  
 FOR THR 5 22 - NYLON 66, UL RATING 94-HB  
 LENS: POLYCARBONATE UL RATING 94-V2  
 LENS RETAINING RING: POLYPROPYLENE  
 LENS SEAL: TPE
  3. OPTICAL CORE ENDS POLISHED TO 10 MICRONS
  4. MOUNTS THROUGH FRONT OF PANEL. COMPRESSION OF THE SEAL IS ACCOMPLISHED BY PRESSING THE RETAINING RING IN PLACE
  5. LENSES MOUNT THROUGH A 9/32" (7.12mm) HOLE ON 3/8" (9.52mm) CENTERS
  6. PANEL THICKNESS 1/32" (0.79mm) TO 1/8" (3.18mm)
  7. FOR BEST RESULTS USE ONLY NARROW VIEWING ANGLE NON-DIFFUSED LEDS WITH OUTPUT POWER GREATER THAN 100mcd
  8. U.S. AND FOREIGN PAT. ISSUED

REVISIONS					
ECN #	REV.	DESCRIPTION	DATE	INITIALS	CHK'D
-	001	INITIAL RELEASE	7/8/09	SMU	AZ
-	002	DWG FORMAT UPDATE	8/2/10	KH	AZ
-	003	REVISED PER ECR 092810AA01	10/4/10	KH	AZ
396	004	REVISED PER ECR 011812KH01	1/20/12	KH	AZ

LITE PIPE ASSEMBLY  
 ORDERING CODE (EXAMPLE): **FLX 322 XXX XX**




LENS TYPE CODE	
322	CMS 322, LOW PROFILE FRESNEL LENS WITH MOISTURE SEAL AND RETAINING RING. MEETS NEMA 4 RATING.

LENS COLOR	
RTP	RED TRANSPARENT
ATP	AMBER TRANSPARENT
GTP	GREEN TRANSPARENT
BTP	BLUE TRANSPARENT
YTP	YELLOW TRANSPARENT
CTP	CLEAR TRANSPARENT
GLO	WHITE TRANSLUCENT

FIBER LENGTH CODE	
02	2.0"
04	4.0"
06	6.0"
08	8.0"
12	12.0"

CUSTOM LENGTHS AVAILABLE UPON REQUEST

MOUNTING OPTIONS  
(ORDER SEPARATELY)



DIMENSION STYLE: INCHES (MM) GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED		APPROVAL		DATE
INCHES	MM	DRAWN	KHOWARD	8/2/10
X	±.020 ±.508	CHECKED	AZANELLI	8/2/10
XX	±.010 ±.254			
XXX	±.005 ±.127			
ANGLE ±1°				
<input checked="" type="checkbox"/> BREAK ALL CORNERS AND SHARP EDGES 90° MAX		MATERIAL		
		SEE NOTES		
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VISUAL COMMUNICATIONS COMPANY, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VISUAL COMMUNICATIONS COMPANY, INC IS PROHIBITED.		FINISH		
		SEE NOTES		
		DO NOT SCALE DRAWING		

**VCC OPTOELECTRONICS**  
 190 Bosstick Boulevard, Suite 101 San Marcos, CA 92069 USA  
 Phone (760) 560-1300 Fax (760) 560-1301 email vccsales@vccite.com

TITLE: **FLX 322 FLEXFIRE FLEXIBLE LITEPIPE**

SIZE	DWG. NO.	REV
<b>B</b>	<b>FLX 322 XXX XX</b>	<b>004</b>

SCALE: 2:1 SHEET 1 OF 1

8 7 6 5 4 3 2 1