



XLR (CHANNEL)	XLRM (DESC.)	CABLE (COLOR)	PIN 2 (RED)	PIN 3 (BLACK)	PIN 1 (BARE)
1	XLRM	BROWN	24	12	25
2	XLRM	RED	10	23	11
3	XLRM	ORANGE	21	9	22
4	XLRM	YELLOW	7	20	8
5	XLRM	GREEN	18	6	19
6	XLRM	BLUE	4	17	5
7	XLRM	PURPLE	15	3	16
8	XLRM	GRAY	1	14	2

NOTES:
 1. BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.

B 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.

B 3. MATERIALS:
 XLR CONNECTORS:
 HANDLE - ZINC ALLOY, NICKEL PLATED
 HOUSING AND LATCH - ZINC ALLOY, NICKEL PLATED
 INSULATOR - THERMOPLASTIC, GREEN
 PINS - SPECIAL COPPER ALLOY, SILVER PLATED
 H.S. TUBING - THERMOPLASTIC
 DSUB:
 CABLE CLAMP - COPPER, NICKEL PLATED
 SHELL - STEEL, TIN PLATED
 INSULATORS - THERMOPLASTIC
 SCREW LOCKS - BRASS, NICKEL PLATED

4. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

REV	ECO NUMBER	DATE	BY	APVD
C	27520	06/08/15	PC	TJK
B	26637	10/4/10	RS	TJK
A	26568	7/20/10	RS	TJK

UNLESS OTHERWISE SPECIFIED
 1. ALL DIMENSIONS IN INCHES [mm]
 - TWO PLACE DECIMALS ±0.02 [0.5]
 - THREE PLACE DECIMALS ±0.005 [0.13]

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE		WIDTH		MULT		LBS/M		TEMPER	
FINISH SPEC No.						MATERIAL SPEC No.			
FIRST USED ON				SCALE 1:2					
DATE DRAWN	BY	CHKD	APVD						
7/16/09	JGK	RS	TJK	11/30/10		SHEET 1 OF 1			
NAME						PART No.		REV	
DB25F TO 8-XLRM, RoHS						DB25FXLRM		C	