

## SATA to eSATA Transition Cable (7Pin/7Pin), 2-ft.

MODEL NUMBER: P952-002



### Highlights

- Connect external eSATA drives to your SATA internal controller card
- 2ft SATA-II rated 6Gbps cable
- Plug-n-Play
- 7pin SATA "L" type connector (Internal) to 7pin "I" type connector (external)

### Description

With Tripp Lite's P952-002, SATA to eSATA bracket/cable, you can connect an external eSATA hard drive to your internal SATA controller. Simply plug the standard 7-pin SATA connector into an available port on your controller card or motherboard, and the bracket into an available external I/O slot. No software to load...completely plug and play. 24" cable provides plenty of length to connect any where inside a PC case. 26AWG cable rated to handle current 6Gbps SATA speeds.

### Features

- Connect external eSATA drives to your SATA internal controller card
- SATA-II rated 6Gbps, 24", 26AWG cable
- Plug-n-Play
- 7pin SATA "L" type connector (Internal) to 7pin "I" type connector (external)

## Specifications

| OVERVIEW           |              |
|--------------------|--------------|
| UPC Code           | 037332145932 |
| Technology         | SATA/eSATA   |
| INPUT              |              |
| Cable Length (ft.) | 2            |
| Cable Length (m)   | 0.6          |
| PHYSICAL           |              |



|                                     |                           |
|-------------------------------------|---------------------------|
| Wire Gauge (AWG)                    | 26                        |
| Shipping Dimensions (hwd / in.)     | 0.50 x 7.00 x 9.50        |
| Shipping Dimensions (hwd / cm)      | 1.27 x 17.78 x 24.13      |
| Shipping Weight (lbs.)              | 0.13                      |
| Shipping Weight (kg)                | 0.06                      |
| Color                               | Red                       |
| <b>ENVIRONMENTAL</b>                |                           |
| Storage Temperature Range           | -20 ~ 65C (-4F ~ 149F)    |
| Operating Temperature               | 0 ~ 40C (32F ~ 104F)      |
| Operating Humidity Range            | 10 to 90%                 |
| Storage Humidity Range              | 20 to 80%                 |
| <b>CONNECTIONS</b>                  |                           |
| Side A - Connector 1                | 7 PIN SATA (MALE)         |
| Side B - Connector 1                | 7 PIN ESATA (MALE)        |
| <b>CERTIFICATIONS</b>               |                           |
| Certifications                      | ROHS                      |
| <b>WARRANTY</b>                     |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>