

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ6.4~7.8
	VOLTAGE		CURRENT	

### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				

<b>REMARK</b> THIS PRODUCT SHALL BE MATED WITH DH3 * B-27S,IT APPLIES TO DH3 * B-27S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.  Unless otherwise specified, refer to JIS C 5402.	APPROVED	KN. ICHIKAWA	10.07.05
	CHECKED	KN. ICHIKAWA	10.07.05
	DESIGNED	TU. TANIGUCHI	10.07.05
	DRAWN	TU. TANIGUCHI	10.07.05

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELG4-126591-00
--	-------------	----------------

<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DH-27-CV2B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0014-6-00	△ 1/1