

## Surge protection device - SYS N4 480D - 2800707

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Combination lightning arrester and TVSS system for ungrounded 480 V Delta systems

### Product description

Combination lightning arrester and TVSS for 480 V Delta. Components are housed in an IP66/NEMA 4 cabinet.



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 10.0 GRM |
| Custom tariff number                 | 85363090 |

### Technical data

#### Dimensions

|        |        |
|--------|--------|
| Height | 500 mm |
| Width  | 400 mm |
| Depth  | 210 mm |

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Degree of protection            | IP66 / NEMA 4    |
| Ambient temperature (operation) | -40 °C ... 80 °C |

#### General

|                                |                          |
|--------------------------------|--------------------------|
| NEMA power supply system       | 480 V Delta              |
| Housing material               | Steel                    |
| Mounting type                  | Surface/Wall mounting    |
| Surge protection fault message | Remote indicator contact |

#### Protective circuit

|                         |        |
|-------------------------|--------|
| IEC test classification | I + II |
|-------------------------|--------|

## Surge protection device - SYS N4 480D - 2800707

### Technical data

#### Protective circuit

|  |                  |
|--|------------------|
| EN type  | T1               |
| Nominal voltage $U_N$  | < 480 V          |
| Maximum continuous operating voltage $U_C$ (L-PE)                | 480 V AC         |
| Impulse discharge current (10/350) $\mu$ s charge                | 25 As            |
| Impulse discharge current (10/350) $\mu$ s, peak value $I_{imp}$ | 50 kA (per mode) |
| Response time  | $\leq$ 25 ns     |
| Follow current quenching capacity If                             | 50 kA            |

#### Connection, protective circuit

|  |                    |
|--|--------------------|
| Connection method                      | Screw connection   |
| Conductor cross section stranded min.  | 16 mm <sup>2</sup> |
| Conductor cross section stranded max.  | 35 mm <sup>2</sup> |
| Conductor cross section solid min.     | 10 mm <sup>2</sup> |
| Conductor cross section solid max.     | 50 mm <sup>2</sup> |
| Conductor cross section AWG/kcmil min. | 6                  |
| Conductor cross section AWG/kcmil max  | 1                  |

#### Remote indicator contact

|  |                      |
|--|----------------------|
| Connection method                      | Screw connection     |
| Conductor cross section stranded min.  | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded max.  | 1.5 mm <sup>2</sup>  |
| Conductor cross section solid min.     | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.     | 1.5 mm <sup>2</sup>  |
| Conductor cross section AWG/kcmil min. | 28                   |
| Conductor cross section AWG/kcmil max  | 16                   |

#### NEMA / UL data

|   |        |
|---|--------|
| UL type   | type 2 |
| Nominal discharge current $I_n$ (without reference direction) | 20 kA  |
| Maximum Surge Current per Phase                               | 50 kA  |
| Short-circuit current rating (SCCR)                           | 50 kA  |

#### Standards and Regulations

|                       |   |
|-----------------------|---|
| Standards/regulations | UL 1449 3 <sup>rd</sup> edition, Sept. 2009 |
|                       | IEC 60643-1                                 |
|                       | EN 61643-11                                 |
|                       | CAN/CSA-C22.2 No. 8                         |

# Surge protection device - SYS N4 480D - 2800707

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140201 |
| eCl@ss 4.1 | 27130801 |
| eCl@ss 5.0 | 27130801 |
| eCl@ss 5.1 | 27130801 |
| eCl@ss 6.0 | 27130802 |
| eCl@ss 7.0 | 27130802 |
| eCl@ss 8.0 | 27130802 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000942 |
| ETIM 4.0 | EC000941 |
| ETIM 5.0 | EC000941 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212010 |
| UNSPSC 7.0901 | 39121610 |
| UNSPSC 11     | 39121610 |
| UNSPSC 12.01  | 39121610 |
| UNSPSC 13.2   | 39121620 |

## Approvals

### Approvals

---

#### Approvals

ETLus / cETL / cETLus

---

#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

|       |
|-------|
| ETLus |
|-------|

# Surge protection device - SYS N4 480D - 2800707

## Approvals

cETL

cETLus

## Drawings

Circuit diagram

