


P1	P2
1 WHITE	6
2 BLACK	5
3 RED	4
4 GREEN	3
5 YELLOW	2
6 BLUE	1

**Note:**  
 • Material: Housing-polycarbonate, clear  
 Terminal-0.36[.014] thick phosphor bronze.  
 Thick gold in localized gold plate.  
 Area, Gold Flash over the remainder.  
 Over 2.54mm[.000100] thick nickel underplate.



Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/6/W-5	A	1,525±20(5ft)	White	1,525-1,535mm
AT-S-26-6/6/W-7	B	2,135±30(7ft)	White	2,135-2,145mm
AT-S-26-6/6/W-10	C	3,050±60(10ft)	White	3,050-3,060mm
AT-S-26-6/6/W-12	D	3,660±60(12ft)	White	3,660-3,670mm
AT-S-26-6/6/W-14	E	4,270±60(14ft)	White	4,270-4,280mm
AT-S-26-6/6/W-25	F	7,625±100(25ft)	White	7,625-7,635mm
AT-S-26-6/6/W-50	G	15,250±150(50ft)	White	15,250-15,260mm



Scale	Free				Date	Name	
TOLERANCE					Drawn	08.07.13	Wilson
X.	±X				Approved	08.07.13	Groll
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name		

Title	
Modular cable - Straight	
6P6C 50µ", 26AWG, White, 5-50 feet	
ASSMANN WSW-No.	
AT-S-26-6/6/W-xx	
Drawing-No.	
Replace	rev00
Sheet	1/1