

Specification Sheet

Part Number: HDM321HIHSUVH4



Medium Torque Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

Article Number	151-07100
Type	HDM321
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Mount and tie combination makes it easy to service bundles in the field.• Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.• Eliminates the needs for multiple sized fix diameter clamps.
Quantity Per	bag

Product Description

The arched H-profile of the saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles, and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

Short Description

Medium Torque Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

Global Part Name

HDM321-PA66HIRHSUV-BK

Length L (Imperial)

1.81

Length L (Metric)

46.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

0.95

Width W (Metric)

24.0

Height H (Imperial)

0.81

Height H (Metric)

20.7

Cable Tie Width Max (Imperial)

0.50

Cable Tie Width Max (Metric)

12.7

Mounting Hole Diameter D (Imperial)

0.3125

Mounting Hole Diameter D (Metric)

8.31 mm

Mounting Hole Diameter D Min (Imperial)

0.3125

Mounting Hole Diameter D Max (Imperial)

0.3125

Mounting Hole Diameter D Max (Metric)

7.9

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Maximum Torque (kgf-cm)	553
Maximum Torque (lbf-ft)	40
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909987
Content Unit(BMEcat)	pcs.
Weight (Imperial)	0.01902

