

280x89mm

AC AXIAL FAN

FKA2-28089 Series



Features:

- Motor: Capacitor-Run Induction Motor
- Motor Protection: Thermal Protected
- Bearing Type: Two Ball
- Connection: UL 1430 AWG 22, 300mm Wire Leads or Terminal
- Frame Material: Aluminum Alloy
- Impeller Material: Plastic UL94V-0
- Operating Temp:
Two Ball: -10°C~70°C
- Life Expectancy:
Two Ball: 50,000 Hours



Fan-S Division



| Model No. | Volt. | Freq. | Current | Power | Rated Speed | Maximum AirFlow | | Maximum Static Pressure | | Noise Level | Weight |
|---------------------|-------|-------|-----------|-------------|-------------|-----------------|---------|-------------------------|-------------|-------------|--------|
| | (VAC) | (Hz) | (A) | (W) | (rpm) | (CMM) | (CFM) | (InAq) | (mmAq) | (dB/A) | (g) |
| FKA2-28089NBM ** 3F | 115 | 50/60 | 0.75/0.66 | 52.70/51.30 | 1450/1700 | 17.687/20.942 | 625/740 | 0.014/0.018 | 0.360/0.460 | 60.0/62.0 | 3500 |
| FKA2-28089QBM ** 3F | 230 | 50/60 | 0.26/0.27 | 52.70/51.30 | 1450/1700 | 17.687/20.942 | 625/740 | 0.014/0.018 | 0.360/0.460 | 60.0/62.0 | 3500 |

** Indicates "W" (Wire Leads) or "T" (Terminal)

Noise is measured at the distance of one (1) meter from the axis of intake.

50Hz



60Hz



ISO-9001 Company

Qualtek
Electronics Corporation

www.qualtekusa.com

REV. C